



Efficiency, Stability, Reliable, Precision

High Power Programmable DC Power System

» Product specification sheet



更多资讯请关注我们的公众号



High Power Programmable DC Power System

Contents

SYS32VDC12000W	01
SYS32VDC24000W	01
SYS32VDC40000W	01
SYS40VDC12000W	02
SYS40VDC24000W	02
SYS40VDC40000W	02
SYS75VDC12000W	03
SYS75VDC24000W	03
SYS75VDC40000W	03
SYS96VDC12000W	04
SYS120VDC12000W	05
SYS120VDC24000W	05
SYS120VDC40000W	05
SYS150VDC12000W	06
SYS150VDC24000W	06
SYS150VDC40000W	06
SYS192VDC24000W	07
SYS200VDC12000W	08
SYS200VDC24000W	08
SYS200VDC40000W	08
SYS225VDC12000W	09
SYS240VDC24000W	10
SYS320VDC40000W	11
SYS360VDC12000W	12
SYS400VDC40000W	13
SYS450VDC12000W	14
SYS450VDC24000W	14
SYS600VDC12000W	15
SYS600VDC24000W	15
SYS600VDC40000W	15
SYS720VDC24000W	16
SYS750VDC40000W	17
SYS800VDC12000W	18
SYS800VDC24000W	18
SYS800VDC40000W	18
SYS900VDC24000W	19
SYS1200VDC24000W	20
SYS1200VDC40000W	20

High Power Programmable DC Power System

Selection List:

Model	Voltage	Current	Power	Corresponding page
SYS32VDC12000W	32V	600A	12kW	P01
SYS32VDC24000W		1200A	24kW	P01
SYS32VDC40000W		2000A	40kW	P01
SYS40VDC12000W	40V	360A	12kW	P02
SYS40VDC24000W		720A	24kW	P02
SYS40VDC40000W		1200A	40kW	P02
SYS75VDC12000W	75V	180A	12kW	P03
SYS75VDC24000W		360A	24kW	P03
SYS75VDC40000W		600A	40kW	P03
SYS96VDC12000W	96V	200A	12kW	P04
SYS120VDC12000W	120V	120A	12kW	P05
SYS120VDC24000W		240A	24kW	P05
SYS120VDC40000W		400A	40kW	P05
SYS150VDC12000W	150V	90A	12kW	P06
SYS150VDC24000W		180A	24kW	P06
SYS150VDC40000W		300A	40kW	P06
SYS192VDC24000W	192V	200A	24kW	P07
SYS200VDC12000W	200V	72A	12kW	P08
SYS200VDC24000W		144A	24kW	P08
SYS200VDC40000W		240A	40kW	P08
SYS225VDC12000W	225V	60A	12kW	P09
SYS240VDC24000W	240V	120A	24kW	P10
SYS320VDC40000W	320V	200A	40kW	P11
SYS360VDC12000W	360V	40A	12kW	P12
SYS400VDC40000W	400V	120A	40kW	P13
SYS450VDC12000W	450V	30A	12kW	P14
SYS450VDC24000W		60A	24kW	P14
SYS600VDC12000W	600V	30A	12kW	P15
SYS600VDC24000W		60A	24kW	P15
SYS600VDC40000W		100A	40kW	P15
SYS720VDC24000W	720V	40A	24kW	P16
SYS750VDC40000W	750V	60A	40kW	P17
SYS800VDC12000W	800V	22.5A	12kW	P18
SYS800VDC24000W		45A	24kW	P18
SYS800VDC40000W		75A	40kW	P18
SYS900VDC24000W	900V	30A	24kW	P19
SYS1200VDC24000W	1200V	24A	24kW	P20
SYS1200VDC40000W		40A	40kW	P20

High Power Programmable DC Power System

SYS32VDC

MODEL	SYS32VDC12000W		SYS32VDC24000W		SYS32VDC40000W	
INPUT						
Voltage	190~265VAC					
Frequency	47~63Hz					
Phase	3 Phase,4Wire+Groud/Y Connect					
Max.Current	75A		150A		250A	
Input Power Max	15kW		28.5kW		47.5kW	
Power Factor at 220VAC Input , Full Load	0.98 Min. Active PFC		0.98 Min. Active PFC		0.98 Min. Active PFC	
Efficiency	>88% Max @Full Load and Units=4kW Model					
OUTPUT						
Output Voltage	0~32V					
Output Current	0~600A		0~1200A		0~2000A	
Output Power	12kW Max		24kW Max		40kW Max	
Load Regulation	Voltage	90mV		180mV		300mV
	Current	0.6A		1.2A		2A
Line Regulation	Voltage	0.02%F.S.+30mV				
	Current	0.02%F.S.+15mA				
Voltage Setting	Range	0~32V				
	Resolution	0.1mV				
	Accuracy	0.1%+0.1%F.S. at 0< Ouput Voltage =<75Vdc 0.05%+0.05%F.S. at 75Vdc< Ouput Voltage =<1200Vdc				
Current Setting	Range	0~600A		0~1200A		0~2000A
	Resolution	10mA		0.1A		0.1A
	Accuracy	0.1%+0.10%F.S				
Ripple	Voltage	120mVp-p/20mVrms				
	Current	600mA(Full Range)		1200mA(Full Range)		2000mA(Full Range)
		300mA(TYP Value)		600mA(TYP Value)		1000mA(TYP Value)
MEASUREMENT						
Voltage Setting	Range	0~32V				
	Resolution	0.1mV				
	Accuracy	0.1%+0.1%F.S. at 0< Ouput Voltage =<75Vdc 0.05%+0.05%F.S. at 75Vdc< Ouput Voltage =<1200Vdc				
Current Setting	Range	0~600A		0~1200A		0~2000A
	Resolution	10mA		0.1A		0.1A
	Accuracy	0.1%+0.10%F.S				
Extra Function						
Remote Sense	Range	4V(DC), Max. Total power less than rated power				
Comm. Responce.	50ms					
Graphic Display	VFD					
Operation Key Feature	Soft key, Numeric key, Rotary Knob					
Rack mount Handles	Yes					
FAN	Temperature Control					
Protection Circuits	OCP, OVP, OPP, OTP, FAN					
Interface	USB, RS485, RS232, LAN(Standard); GPIB(Option)					
Remote Control Input/Output signal characteristics						
Remote Input signal	Not Support					
Remote output signal	Not Support					
Environmental						
Operating Temperature	0°C~40°C					
Storage Temperature	-20°C~70°C					
Altitude	2000m					
Relative Humidity	10%-90%, non-condensing					
Temperature Coefficient	100ppm/°C at Voltage, 300ppm/°C at Current					
Mechanical						
Dimensions(W*H*D)	600.0*696.0*700.0 mm		600.0*963.0*700.0 mm		600.0*1338.0*700.0 mm	
Package Dimensions(W*H*D)	720.0*880.0*820.0 mm		720.0*1160.0*820.0 mm		720.0*1535.0*820.0 mm	
Unit Net Weight	54kg+15kg*3 (REF)		100.0kg+15kg*6 (REF)		120.0kg+15kg*10 (REF)	
Accessories Weight	0.4kg					
Shipping Weight	94kg+15kg*3 (REF)		160.0kg+15kg*6 (REF)		200.0kg+15kg*10 (REF)	
Regulatory Compliance						
CE Mark	Installation Overvltage Category II; Class II equipment; indoor use only.					

*F.S. represents the maximum value of the output range .

*N stands for the number of installed power supply units, and N is greater than 1 .

All specifications are subject to change without notice.

High Power Programmable DC Power System

SYS40VDC

MODEL	SYS40VDC12000W		SYS40VDC24000W		SYS40VDC40000W		
INPUT							
Voltage	190~265VAC						
Frequency	47~63Hz						
Phase	3 Phase,4Wire+Groud/Y Connect						
Max.Current	75A		150A		250A		
Input Power Max	15kW		28.5kW		47.5kW		
Power Factor at 220VAC Input , Full Load	0.98 Min. Active PFC		0.98 Min. Active PFC		0.98 Min. Active PFC		
Efficiency	>88% Max @Full Load and Units=4kW Model						
OUTPUT							
Output Voltage	0~40V						
Output Current	0~360A		0~720A		0~1200A		
Output Power	12kW Max		24kW Max		40kW Max		
Load Regulation	Voltage	120mV		240mV		400mV	
	Current	0.36A		0.75A		1.2A	
Line Regulation	Voltage	0.02%F.S.+30mV					
	Current	0.02%F.S.+15mA					
Voltage Setting	Range	0~40V					
	Resolution	0.1mV					
	Accuracy	0.1%+0.1%F.S. at 0< Ouput Voltage =<75Vdc 0.05%+0.05%F.S. at 75Vdc< Ouput Voltage =<1200Vdc					
Current Setting	Range	0~360A		0~720A		0~1200A	
	Resolution	10mA		10mA		0.1A	
	Accuracy	0.1%+0.10%F.S					
Ripple	Voltage	80mVp-p/12mVrms					
	Current	225mA(Full Range)		450mA(Full Range)		750mA(Full Range)	
		30mA(TYP Value)		60mA(TYP Value)		100mA(TYP Value)	
MEASUREMENT							
Voltage Setting	Range	0~40V					
	Resolution	0.1mV					
	Accuracy	0.1%+0.1%F.S. at 0< Ouput Voltage =<75Vdc 0.05%+0.05%F.S. at 75Vdc< Ouput Voltage =<1200Vdc					
Current Setting	Range	0~360A		0~720A		0~1200A	
	Resolution	10mA		10mA		0.1A	
	Accuracy	0.1%+0.10%F.S					
Extra Function							
Remote Sense	Range	5V(DC), Max. Total power less than rated power					
Comm. Responce.	50ms						
Graphic Display	VFD						
Operation Key Feature	Soft key, Numeric key, Rotary Knob						
Rack mount Handles	Yes						
FAN	Temperature Control						
Protection Circuits	OCP, OVP, OPP, OTP, FAN						
Interface	USB, RS485, RS232, LAN(Standard); GPIB(Option)						
Remote Control Input/Output signal characteristics							
Remote Input signal	Not Support						
Remote output signal	Not Support						
Environmental							
Operating Temperature	0°C~40°C						
Storage Temperature	-20°C~70°C						
Altitude	2000m						
Relative Humidity	10%-90%, non-condensing						
Temperature Coefficient	100ppm/°C at Voltage, 300ppm/°C at Current						
Mechanical							
Dimensions(W*H*D)	600.0*696.0*700.0 mm		600.0*963.0*700.0 mm		600.0*1338.0*700.0 mm		
Package Dimensions(W*H*D)	720.0*880.0*820.0 mm		720.0*1160.0*820.0 mm		720.0*1535.0*820.0 mm		
Unit Net Weight	54kg+15kg*3 (REF)		100.0kg+15kg*6 (REF)		120.0kg+15kg*10 (REF)		
Accessories Weight	0.4kg						
Shipping Weight	94kg+15kg*3 (REF)		160.0kg+15kg*6 (REF)		200.0kg+15kg*10 (REF)		
Regulatory Compliance							
CE Mark	Installation Overvltage Category II; Class II equipment; indoor use only.						

*F.S. represents the maximum value of the output range .

*N stands for the number of installed power supply units, and N is greater than 1 .

All specifications are subject to change without notice.

High Power Programmable DC Power System

SYS75VDC

MODEL		SYS75VDC12000W	SYS75VDC24000W	SYS75VDC40000W
INPUT				
Voltage		190~265VAC		
Frequency		47~63Hz		
Phase		3 Phase,4Wire+Groud/Y Connect		
Max.Current		75A	150A	250A
Input Power Max		15kW	28.5kW	47.5kW
Power Factor at 220VAC Input , Full Load		0.98 Min. Active PFC	0.98 Min. Active PFC	0.98 Min. Active PFC
Efficiency		>88% Max @Full Load and Units=4kW Model		
OUTPUT				
Output Voltage		0~75V		
Output Current		0~180A	0~360A	0~600A
Output Power		12kW Max	24kW Max	40kW Max
Load Regulation	Voltage	120mV	240mV	400mV
	Current	0.18A	0.36A	0.6A
Line Regulation	Voltage	0.02%F.S.+30mV		
	Current	0.02%F.S.+15mA		
Voltage Setting	Range	0~75V		
	Resolution	0.1mV		
	Accuracy	0.1%+0.1%F.S. at 0< Ouput Voltage =<75Vdc 0.05%+0.05%F.S. at 75Vdc< Ouput Voltage =<1200Vdc		
Current Setting	Range	0~180A	0~360A	0~600A
	Resolution	10mA		
	Accuracy	0.1%+0.10%F.S		
Ripple	Voltage	80mVp-p/16mVrms		
	Current	90mA(Full Range)	180mA(Full Range)	300mA(Full Range)
		15mA(TYP Value)	30mA(TYP Value)	50mA(TYP Value)
MEASUREMENT				
Voltage Setting	Range	0~75V		
	Resolution	0.1mV		
	Accuracy	0.1%+0.1%F.S. at 0< Ouput Voltage =<75Vdc 0.05%+0.05%F.S. at 75Vdc< Ouput Voltage =<1200Vdc		
Current Setting	Range	0~180A	0~360A	0~600A
	Resolution	10mA		
	Accuracy	0.1%+0.10%F.S		
Extra Function				
Remote Sense	Range	5V(DC), Max. Total power less than rated power		
Comm. Respondence.		50ms		
Graphic Display		VFD		
Operation Key Feature		Soft key, Numeric key, Rotary Knob		
Rack mount Handles		Yes		
FAN		Temperature Control		
Protection Circuits		OCP, OVP, OPP, OTP, FAN		
Interface		USB, RS485, RS232, LAN(Standard); GPIB(Option)		
Remote Control Input/Output signal characteristics				
Remote Input signal		Not Support		
Remote output signal		Not Support		
Environmental				
Operating Temperature		0°C~40°C		
Storage Temperature		-20°C~70°C		
Altitude		2000m		
Relative Humidity		10%-90%, non-condensing		
Temperature Coefficient		100ppm/°C at Voltage, 300ppm/°C at Current		
Mechanical				
Dimensions(W*H*D)		600.0*696.0*700.0 mm	600.0*963.0*700.0 mm	600.0*1338.0*700.0 mm
Package Dimensions(W*H*D)		720.0*880.0*820.0 mm	720.0*1160.0*820.0 mm	720.0*1535.0*820.0 mm
Unit Net Weight		54kg+15kg*3 (REF)	100.0kg+15kg*6 (REF)	120.0kg+15kg*10 (REF)
Accessories Weight		0.4kg		
Shipping Weight		94kg+15kg*3 (REF)	160.0kg+15kg*6 (REF)	200.0kg+15kg*10 (REF)
Regulatory Compliance				
CE Mark		Installation Overvltage Category II; Class II equipment; indoor use only.		

*F.S. represents the maximum value of the output range .

*N stands for the number of installed power supply units, and N is greater than 1 .

All specifications are subject to change without notice.

High Power Programmable DC Power System

SYS96VDC

MODEL		SYS96VDC12000W
INPUT		
Voltage	190~265VAC	
Frequency	47~63Hz	
Phase	3 Phase,4Wire+Groud/Y Connect	
Max.Current	75A	
Input Power Max	15kW	
Power Factor at 220VAC Input , Full Load	0.98 Min. Active PFC	
Efficiency	>88% Max @Full Load and Units=4kW Model	
OUTPUT		
Output Voltage	0~96V	
Output Current	0~200A	
Output Power	12kW Max	
Load Regulation	Voltage	90mV
	Current	0.6A
Line Regulation	Voltage	0.02%F.S.+30mV
	Current	0.02%F.S.+15mA
Voltage Setting	Range	0~96V
	Resolution	1mV
	Accuracy	0.1%+0.1%F.S. at 0< Ouput Voltage =<75Vdc 0.05%+0.05%F.S. at 75Vdc< Ouput Voltage =<1200Vdc
Current Setting	Range	0~200A
	Resolution	1mA
	Accuracy	0.1%+0.10%F.S
Ripple	Voltage	90mVp-p/15mVrms
	Current	800mA(Full Range) 400mA(TYP Value)
MEASUREMENT		
Voltage Setting	Range	0~96V
	Resolution	1mV
	Accuracy	0.1%+0.1%F.S. at 0< Ouput Voltage =<75Vdc 0.05%+0.05%F.S. at 75Vdc< Ouput Voltage =<1200Vdc
Current Setting	Range	0~200A
	Resolution	1mA
	Accuracy	0.1%+0.10%F.S
Extra Function		
Remote Sense	Range	4V(DC), Max. Total power less than rated power
Comm. Respondence.	50ms	
Graphic Display	VFD	
Operation Key Feature	Soft key, Numeric key, Rotary Knob	
Rack mount Handles	Yes	
FAN	Temperature Control	
Protection Circuits	OCP, OVP, OPP, OTP, FAN	
Interface	USB, RS485, RS232, LAN(Standard); GPIB(Option)	
Remote Control Input/Output signal characteristics		
Remote Input signal	Not Support	
Remote output signal	Not Support	
Environmental		
Operating Temperature	0°C~40°C	
Storage Temperature	-20°C~70°C	
Altitude	2000m	
Relative Humidity	10%-90%, non-condensing	
Temperature Coefficient	100ppm/°C at Voltage, 300ppm/°C at Current	
Mechanical		
Dimensions(W*H*D)	600.0*696.0*700.0 mm	
Package Dimensions(W*H*D)	720.0*880.0*820.0 mm	
Unit Net Weight	54kg+15kg*3 (REF)	
Accessories Weight	0.4kg	
Shipping Weight	94kg+15kg*3 (REF)	
Regulatory Compliance		
CE Mark	Installation Overvltage Category II; Class II equipment; indoor use only.	

*F.S. represents the maximum value of the output range .

*N stands for the number of installed power supply units, and N is greater than 1 .

All specifications are subject to change without notice.

High Power Programmable DC Power System

SYS120VDC

MODEL	SYS120VDC12000W		SYS120VDC24000W	SYS120VDC40000W
INPUT				
Voltage	190~265VAC			
Frequency	47~63Hz			
Phase	3 Phase,4Wire+Groud/Y Connect			
Max.Current	75A	150A	250A	
Input Power Max	15kW	28.5kW	47.5kW	
Power Factor at 220VAC Input , Full Load	0.98 Min. Active PFC	0.98 Min. Active PFC	0.98 Min. Active PFC	
Efficiency	>88% Max @Full Load and Units=4kW Model			
OUTPUT				
Output Voltage	0~120V			
Output Current	0~120A	0~240A	0~400A	
Output Power	12kW Max	24kW Max	40kW Max	
Load Regulation	Voltage	120mV	240mV	400mV
	Current	0.12A	0.24A	0.4A
Line Regulation	Voltage	0.02%F.S.+30mV		
	Current	0.02%F.S.+15mA		
Voltage Setting	Range	0~120V		
	Resolution	1mV		
	Accuracy	0.1%+0.1%F.S. at 0< Ouput Voltage =<75Vdc 0.05%+0.05%F.S. at 75Vdc< Ouput Voltage =<1200Vdc		
Current Setting	Range	0~120A	0~240A	0~400A
	Resolution	10mA		
	Accuracy	0.1%+0.10%F.S		
Ripple	Voltage	160mVp-p/30mVrms		
	Current	90mA(Full Range)	180mA(Full Range)	300mA(Full Range)
		15mA(TYP Value)	30mA(TYP Value)	50mA(TYP Value)
MEASUREMENT				
Voltage Setting	Range	0~120V		
	Resolution	0.1mV	1mV	1mV
	Accuracy	0.1%+0.1%F.S. at 0< Ouput Voltage =<75Vdc 0.05%+0.05%F.S. at 75Vdc< Ouput Voltage =<1200Vdc		
Current Setting	Range	0~120A	0~240A	0~400A
	Resolution	10mA		
	Accuracy	0.1%+0.10%F.S		
Extra Function				
Remote Sense	Range	5V(DC), Max. Total power less than rated power		
Comm. Responce.	50ms			
Graphic Display	VFD			
Operation Key Feature	Soft key, Numeric key, Rotary Knob			
Rack mount Handles	Yes			
FAN	Temperature Control			
Protection Circuits	OCP, OVP, OPP, OTP, FAN			
Interface	USB, RS485, RS232, LAN(Standard); GPIB(Option)			
Remote Control Input/Output signal characteristics				
Remote Input signal	Not Support			
Remote output signal	Not Support			
Environmental				
Operating Temperature	0°C~40°C			
Storage Temperature	-20°C~70°C			
Altitude	2000m			
Relative Humidity	10%-90%, non-condensing			
Temperature Coefficient	100ppm/°C at Voltage, 300ppm/°C at Current			
Mechanical				
Dimensions(W*H*D)	600.0*696.0*700.0 mm	600.0*963.0*700.0 mm	600.0*1338.0*700.0 mm	
Package Dimensions(W*H*D)	720.0*880.0*820.0 mm	720.0*1160.0*820.0 mm	720.0*1535.0*820.0 mm	
Unit Net Weight	4kg+15kg*3 (REF)	100.0kg+15kg*6 (REF)	120.0kg+15kg*10 (REF)	
Accessories Weight	0.4kg			
Shipping Weight	94kg+15kg*3 (REF)	160.0kg+15kg*6 (REF)	200.0kg+15kg*10 (REF)	
Regulatory Compliance				
CE Mark	Installation Overvltage Category II; Class II equipment; indoor use only.			

*F.S. represents the maximum value of the output range .

*N stands for the number of installed power supply units, and N is greater than 1 .

All specifications are subject to change without notice.

High Power Programmable DC Power System

SYS150VDC

MODEL	SYS150VDC12000W		SYS150VDC24000W	SYS150VDC40000W
INPUT				
Voltage	190~265VAC			
Frequency	47~63Hz			
Phase	3 Phase,4Wire+Groud/Y Connect			
Max.Current	75A	150A	250A	
Input Power Max	15kW	28.5kW	47.5kW	
Power Factor at 220VAC Input , Full Load	0.98 Min. Active PFC	0.98 Min. Active PFC	0.98 Min. Active PFC	
Efficiency	>88% Max @Full Load and Units=4kW Model			
OUTPUT				
Output Voltage	0~150V			
Output Current	0~90A	0~180A	0~300A	
Output Power	12kW Max	24kW Max	40kW Max	
Load Regulation	Voltage	120mV	240mV	400mV
	Current	0.09A	0.18A	0.3A
Line Regulation	Voltage	0.02%F.S.+30mV		
	Current	0.02%F.S.+15mA		
Voltage Setting	Range	0~150V		
	Resolution	1mV		
	Accuracy	0.1%+0.1%F.S. at 0< Ouput Voltage =<75Vdc 0.05%+0.05%F.S. at 75Vdc< Ouput Voltage =<1200Vdc		
Current Setting	Range	0~90A	0~180A	0~300A
	Resolution	1mA	10mA	10mA
	Accuracy	0.1%+0.10%F.S		
Ripple	Voltage	160mVp-p/30mVrms		
	Current	90mA(Full Range)	180mA(Full Range)	300mA(Full Range)
		15mA(TYP Value)	30mA(TYP Value)	50mA(TYP Value)
MEASUREMENT				
Voltage Setting	Range	0~150V		
	Resolution	1mV		
	Accuracy	0.1%+0.1%F.S. at 0< Ouput Voltage =<75Vdc 0.05%+0.05%F.S. at 75Vdc< Ouput Voltage =<1200Vdc		
Current Setting	Range	0~90A	0~180A	0~300A
	Resolution	1mA	10mA	10mA
	Accuracy	0.1%+0.10%F.S		
Extra Function				
Remote Sense	Range	5V(DC), Max. Total power less than rated power		
Comm. Respondence.	50ms			
Graphic Display	VFD			
Operation Key Feature	Soft key, Numeric key, Rotary Knob			
Rack mount Handles	Yes			
FAN	Temperature Control			
Protection Circuits	OCP, OVP, OPP, OTP, FAN			
Interface	USB, RS485, RS232, LAN(Standard); GPIB(Optional)			
Remote Control Input/Output signal characteristics				
Remote Input signal	Not Support			
Remote output signal	Not Support			
Environmental				
Operating Temperature	0°C~40°C			
Storage Temperature	-20°C~70°C			
Altitude	2000m			
Relative Humidity	10%-90%, non-condensing			
Temperature Coefficient	100ppm/°C at Voltage, 300ppm/°C at Current			
Mechanical				
Dimensions(W*H*D)	600.0*696.0*700.0 mm	600.0*963.0*700.0 mm	600.0*1338.0*700.0 mm	
Package Dimensions(W*H*D)	720.0*880.0*820.0 mm	720.0*1160.0*820.0 mm	720.0*1535.0*820.0 mm	
Unit Net Weight	54kg+15kg*3 (REF)	100.0kg+15kg*6 (REF)	120.0kg+15kg*10 (REF)	
Accessories Weight	0.4kg			
Shipping Weight	94kg+15kg*3 (REF)	160.0kg+15kg*6 (REF)	200.0kg+15kg*10 (REF)	
Regulatory Compliance				
CE Mark	Installation Overvltage Category II; Class II equipment; indoor use only.			

*F.S. represents the maximum value of the output range.

*N stands for the number of installed power supply units, and N is greater than 1.

All specifications are subject to change without notice.

High Power Programmable DC Power System

SYS192VDC		SYS192VDC24000W	
INPUT			
Voltage	190~265VAC		
Frequency	47~63Hz		
Phase	3 Phase,4Wire+Groud/Y Connect		
Max.Current	150A		
Input Power Max	28.5kW		
Power Factor at 220VAC Input , Full Load	0.98 Min. Active PFC	0.98 Min. Active PFC	0.98 Min. Active PFC
Efficiency	>88% Max @Full Load and Units=4kW Model		
OUTPUT			
Output Voltage	0~192V		
Output Current	0~200A		
Output Power	24kW Max		
Load Regulation	Voltage	180mV	
	Current	1.2A	
Line Regulation	Voltage	0.02%F.S.+30mV	
	Current	0.02%F.S.+15mA	
Voltage Setting	Range	0~192V	
	Resolution	10mV	
	Accuracy	0.1%+0.1%F.S. at 0< Ouput Voltage =<75Vdc 0.05%+0.05%F.S. at 75Vdc< Ouput Voltage =<1200Vdc	
Current Setting	Range	0~200A	
	Resolution	1mA	
	Accuracy	0.1%+0.10%F.S	
Ripple	Voltage	180mVp-p/30mVrms	
	Current	800mA(Full Range)	
		400mA(TYP Value)	
MEASUREMENT			
Voltage Setting	Range	0~192V	
	Resolution	10mV	
	Accuracy	0.1%+0.1%F.S. at 0< Ouput Voltage =<75Vdc 0.05%+0.05%F.S. at 75Vdc< Ouput Voltage =<1200Vdc	
Current Setting	Range	0~200A	
	Resolution	1mA	
	Accuracy	0.1%+0.10%F.S	
Extra Function			
Remote Sense	Range	4V(DC), Max. Total power less than rated power	
Comm. Respondence.	50ms		
Graphic Display	VFD		
Operation Key Feature	Soft key, Numeric key, Rotary Knob		
Rack mount Handles	Yes		
FAN	Temperature Control		
Protection Circuits	OCP, OVP, OPP, OTP, FAN		
Interface	USB, RS485, RS232, LAN(Standard); GPIB(Option)		
Remote Control Input/Output signal characteristics			
Remote Input signal	Not Support		
Remote output signal	Not Support		
Environmental			
Operating Temperature	0°C~40°C		
Storage Temperature	-20°C~70°C		
Altitude	2000m		
Relative Humidity	10%-90%, non-condensing		
Temperature Coefficient	100ppm/°C at Voltage, 300ppm/°C at Current		
Mechanical			
Dimensions(W*H*D)	600.0*963.0*700.0 mm		
Package Dimensions (W*H*D)	720.0*1160.0*820.0 mm		
Unit Net Weight	100.0kg+15kg*6 (REF)		
Accessories Weight	0.4kg		
Shipping Weight	160.0kg+15kg*6 (REF)		
Regulatory Compliance			
CE Mark	Installation Overvltage Category II; Class II equipment; indoor use only.		

*F.S. represents the maximum value of the output range .

*N stands for the number of installed power supply units, and N is greater than 1 .

All specifications are subject to change without notice.

High Power Programmable DC Power System

SYS200VDC

MODEL		SYS200VDC12000W	SYS200VDC24000W	SYS200VDC40000W
INPUT				
Voltage		190~265VAC		
Frequency		47~63Hz		
Phase		3 Phase,4Wire+Groud/Y Connect		
Max.Current		75A	150A	250A
Input Power Max		15kW	28.5kW	47.5kW
Power Factor at 220VAC Input , Full Load		0.98 Min. Active PFC	0.98 Min. Active PFC	0.98 Min. Active PFC
Efficiency		>88% Max @Full Load and Units=4kW Model		
OUTPUT				
Output Voltage		0~200V		
Output Current		0~72A	0~144A	0~240A
Output Power		12kW Max	24kW Max	40kW Max
Load Regulation	Voltage	180mV	360mV	600mV
	Current	72mA	144mA	240mA
Line Regulation	Voltage	0.02%F.S.+30mV		
	Current	0.02%F.S.+15mA		
Voltage Setting	Range	0~200V		
	Resolution	1mV		
	Accuracy	0.1%+0.1%F.S. at 0< Ouput Voltage =<75Vdc 0.05%+0.05%F.S. at 75Vdc< Ouput Voltage =<1200Vdc		
Current Setting	Range	0~72A	0~144A	0~240A
	Resolution	1mA	10mA	10mA
	Accuracy	0.1%+0.10%F.S		
Ripple	Voltage	300mVp-p/60mVrms		
	Current	75mA(Full Range)	150mA(Full Range)	250mA(Full Range)
		30mA(TYP Value)	60mA(TYP Value)	100mA(TYP Value)
MEASUREMENT				
Voltage Setting	Range	0~200V		
	Resolution	1mV		
	Accuracy	0.1%+0.1%F.S. at 0< Ouput Voltage =<75Vdc 0.05%+0.05%F.S. at 75Vdc< Ouput Voltage =<1200Vdc		
Current Setting	Range	0~72A	0~144A	0~240A
	Resolution	1mA	10mA	10mA
	Accuracy	0.1%+0.10%F.S		
Extra Function				
Remote Sense	Range	5V(DC), Max. Total power less than rated power		
Comm. Responce.		50ms		
Graphic Display		VFD		
Operation Key Feature		Soft key, Numeric key, Rotary Knob		
Rack mount Handles		Yes		
FAN		Temperature Control		
Protection Circuits		OCP, OVP, OPP, OTP, FAN		
Interface		USB, RS485, RS232, LAN(Standard); GPIB(Option)		
Remote Control Input/Output signal characteristics				
Remote Input signal		Not Support		
Remote output signal		Not Support		
Environmental				
Operating Temperature		0°C~40°C		
Storage Temperature		-20°C~70°C		
Altitude		2000m		
Relative Humidity		10%-90%, non-condensing		
Temperature Coefficient		100ppm/°C at Voltage, 300ppm/°C at Current		
Mechanical				
Dimensions(W*H*D)		600.0*696.0*700.0 mm	600.0*963.0*700.0 mm	600.0*1338.0*700.0 mm
Package Dimensions (W*H*D)		720.0*880.0*820.0 mm	720.0*1160.0*820.0 mm	720.0*1535.0*820.0 mm
Unit Net Weight		54kg+15kg*3 (REF)	100.0kg+15kg*6 (REF)	120.0kg+15kg*10 (REF)
Accessories Weight		0.4kg		
Shipping Weight		94kg+15kg*3 (REF)	160.0kg+15kg*6 (REF)	200.0kg+15kg*10 (REF)
Regulatory Compliance				
CE Mark		Installation Overvltage Category II; Class II equipment; indoor use only.		

*F.S. represents the maximum value of the output range .

*N stands for the number of installed power supply units, and N is greater than 1 .

All specifications are subject to change without notice.

High Power Programmable DC Power System

SYS225VDC

MODEL		SYS225VDC12000W
INPUT		
Voltage	190~265VAC	
Frequency	47~63Hz	
Phase	3 Phase,4Wire+Groud/Y Connect	
Max.Current	75A	
Input Power Max	15kW	
Power Factor at 220VAC Input , Full Load	0.98 Min. Active PFC	
Efficiency	>88% Max @Full Load and Units=4kW Model	
OUTPUT		
Output Voltage	0~225V	
Output Current	0~60A	
Output Power	12kW Max	
Load Regulation	Voltage	120mV
	Current	0.18A
Line Regulation	Voltage	0.02%F.S.+30mV
	Current	0.02%F.S.+15mA
Voltage Setting	Range	0~225V
	Resolution	10mV
	Accuracy	0.1%+0.1%F.S. at 0< Ouput Voltage =<75Vdc 0.05%+0.05%F.S. at 75Vdc< Ouput Voltage =<1200Vdc
Current Setting	Range	0~60A
	Resolution	0.1mA
	Accuracy	0.1%+0.10%F.S
Ripple	Voltage	60mVp-p/12mVrms
	Current	120mA(Full Range),20mA(TYP Value)
MEASUREMENT		
Voltage Setting	Range	0~225V
	Resolution	10mV
	Accuracy	0.1%+0.1%F.S. at 0< Ouput Voltage =<75Vdc 0.05%+0.05%F.S. at 75Vdc< Ouput Voltage =<1200Vdc
Current Setting	Range	0~60A
	Resolution	0.1mA
	Accuracy	0.1%+0.10%F.S
Extra Function		
Remote Sense	Range	5V(DC), Max. Total power less than rated power
Comm. Responce.	50ms	
Graphic Display	VFD	
Operation Key Feature	Soft key, Numeric key, Rotary Knob	
Rack mount Handles	Yes	
FAN	Temperature Control	
Protection Circuits	OCP, OVP, OPP, OTP, FAN	
Interface	USB, RS485, RS232, LAN(Standard); GPIB(Option)	
Remote Control Input/Output signal characteristics		
Remote Input signal	Not Support	
Remote output signal	Not Support	
Environmental		
Operating Temperature	0°C~40°C	
Storage Temperature	-20°C~70°C	
Altitude	2000m	
Relative Humidity	10%-90%, non-condensing	
Temperature Coefficient	100ppm/°C at Voltage, 300ppm/°C at Current	
Mechanical		
Dimensions(W*H*D)	600.0*696.0*700.0 mm	
Package Dimensions(W*H*D)	720.0*880.0*820.0 mm	
Unit Net Weight	54kg+15kg*3 (REF)	
Accessories Weight	0.4kg	
Shipping Weight	94kg+15kg*3 (REF)	
Regulatory Compliance		
CE Mark	Installation Overvltage Category II; Class II equipment; indoor use only.	

*F.S. represents the maximum value of the output range.

*N stands for the number of installed power supply units, and N is greater than 1.

All specifications are subject to change without notice.

High Power Programmable DC Power System

SYS240VDC系列

MODEL		SYS240VDC24000W
INPUT		
Voltage	190~265VAC	
Frequency	47~63Hz	
Phase	3 Phase,4Wire+Groud/Y Connect	
Max.Current	150A	
Input Power Max	28.5kW	
Power Factor at 220VAC Input , Full Load	0.98 Min. Active PFC	
Efficiency	>88% Max @Full Load and Units=4kW Model	
OUTPUT		
Output Voltage	0~240V	
Output Current	0~120A	
Output Power	24kW Max	
Load Regulation	Voltage	240mV
	Current	0.75A
Line Regulation	Voltage	0.02%F.S.+30mV
	Current	0.02%F.S.+15mA
Voltage Setting	Range	0~240V
	Resolution	10mV
	Accuracy	0.1%+0.1%F.S. at 0< Ouput Voltage =<75Vdc 0.05%+0.05%F.S. at 75Vdc< Ouput Voltage =<1200Vdc
Current Setting	Range	0~120A
	Resolution	1mA
	Accuracy	0.1%+0.10%F.S
Ripple	Voltage	120mVp-p/18mVrms
	Current	300mA(Full Range),40mA(TYP Value)
MEASUREMENT		
Voltage Setting	Range	0~240V
	Resolution	10mV
	Accuracy	0.1%+0.1%F.S. at 0< Ouput Voltage =<75Vdc 0.05%+0.05%F.S. at 75Vdc< Ouput Voltage =<1200Vdc
Current Setting	Range	0~120A
	Resolution	1mA
	Accuracy	0.1%+0.10%F.S
Extra Function		
Remote Sense	Range	5V(DC), Max. Total power less than rated power
Comm. Respondence.	50ms	
Graphic Display	VFD	
Operation Key Feature	Soft key, Numeric key, Rotary Knob	
Rack mount Handles	Yes	
FAN	Temperature Control	
Protection Circuits	OCP, OVP, OPP, OTP, FAN	
Interface	USB, RS485, RS232, LAN(Standard); GPIB(Option)	
Remote Control Input/Output signal characteristics		
Remote Input signal	Not Support	
Remote output signal	Not Support	
Environmental		
Operating Temperature	0°C~40°C	
Storage Temperature	-20°C~70°C	
Altitude	2000m	
Relative Humidity	10%-90%, non-condensing	
Temperature Coefficient	100ppm/°C at Voltage, 300ppm/°C at Current	
Mechanical		
Dimensions(W*H*D)	600.0*963.0*700.0 mm	
Package Dimensions(W*H*D)	720.0*1160.0*820.0 mm	
Unit Net Weight	100.0kg+15kg*6 (REF)	
Accessories Weight	0.4kg	
Shipping Weight	160.0kg+15kg*6 (REF)	
Regulatory Compliance		
CE Mark	Installation Overvltage Category II; Class II equipment; indoor use only.	

*F.S. represents the maximum value of the output range .

*N stands for the number of installed power supply units, and N is greater than 1 .

All specifications are subject to change without notice.

High Power Programmable DC Power System

SYS320VDC

MODEL		SYS320VDC40000W
INPUT		
Voltage	190~265VAC	
Frequency	47~63Hz	
Phase	3 Phase,4Wire+Groud/Y Connect	
Max.Current	250A	
Input Power Max	47.5kW	
Power Factor at 220VAC Input , Full Load	0.98 Min. Active PFC	
Efficiency	> 88% Max @Full Load and Units=4kW Model	
OUTPUT		
Output Voltage	0~320V	
Output Current	0~200A	
Output Power	40kW Max	
Load Regulation	Voltage	300mV
	Current	2A
Line Regulation	Voltage	0.02%F.S.+30mV
	Current	0.02%F.S.+15mA
Voltage Setting	Range	0~320V
	Resolution	10mV
	Accuracy	0.1%+0.1%F.S. at 0< Ouput Voltage =<75Vdc 0.05%+0.05%F.S. at 75Vdc< Ouput Voltage =<1200Vdc
Current Setting	Range	0~200A
	Resolution	1mA
	Accuracy	0.1%+0.10%F.S
Ripple	Voltage	300mVp-p/50mVrms
	Current	800mA(Full Range),400mA(TYP Value)
MEASUREMENT		
Voltage Setting	Range	0~320V
	Resolution	10mV
	Accuracy	0.1%+0.1%F.S. at 0< Ouput Voltage =<75Vdc 0.05%+0.05%F.S. at 75Vdc< Ouput Voltage =<1200Vdc
Current Setting	Range	0~200A
	Resolution	1mA
	Accuracy	0.1%+0.10%F.S
Extra Function		
Remote Sense	Range	4V(DC), Max. Total power less than rated power
Comm. Respondence.	50ms	
Graphic Display	VFD	
Operation Key Feature	Soft key, Numeric key, Rotary Knob	
Rack mount Handles	Yes	
FAN	Temperature Control	
Protection Circuits	OCP, OVP, OPP, OTP, FAN	
Interface	USB, RS485, RS232, LAN(Standard); GPIB(Optional)	
Remote Control Input/Output signal characteristics		
Remote Input signal	Not Support	
Remote output signal	Not Support	
Environmental		
Operating Temperature	0°C~40°C	
Storage Temperature	-20°C~70°C	
Altitude	2000m	
Relative Humidity	10%-90%, non-condensing	
Temperature Coefficient	100ppm/°C at Voltage, 300ppm/°C at Current	
Mechanical		
Dimensions(W*H*D)	600.0*1338.0*700.0 mm	
Package Dimensions(W*H*D)	720.0*1535.0*820.0 mm	
Unit Net Weight	120.0kg+15kg*10 (REF)	
Accessories Weight	0.4kg	
Shipping Weight	200.0kg+15kg*10 (REF)	
Regulatory Compliance		
CE Mark	Installation Overvltage Category II; Class II equipment; indoor use only.	

*F.S. represents the maximum value of the output range.

*N stands for the number of installed power supply units, and N is greater than 1.

All specifications are subject to change without notice.

High Power Programmable DC Power System

SYS360VDC

MODEL		SYS360VDC12000W
INPUT		
Voltage	190~265VAC	
Frequency	47~63Hz	
Phase	3 Phase,4Wire+Groud/Y Connect	
Max.Current	75A	
Input Power Max	15kW	
Power Factor at 220VAC Input , Full Load	0.98 Min. Active PFC	
Efficiency	> 88% Max @Full Load and Units=4kW Model	
OUTPUT		
Output Voltage	0~360V	
Output Current	0~40A	
Output Power	12kW Max	
Load Regulation	Voltage	120mV
	Current	0.12A
Line Regulation	Voltage	0.02%F.S.+30mV
	Current	0.02%F.S.+15mA
Voltage Setting	Range	0~360V
	Resolution	10mV
	Accuracy	0.1%+0.1%F.S. at 0< Ouput Voltage =<75Vdc 0.05%+0.05%F.S. at 75Vdc< Ouput Voltage =<1200Vdc
Current Setting	Range	0~40A
	Resolution	0.1mA
	Accuracy	0.1%+0.10%F.S
Ripple	Voltage	120mVp-p/22.5mVrms
	Current	120mA(Full Range),20mA(TYP Value)
MEASUREMENT		
Voltage Setting	Range	0~360V
	Resolution	10mV
	Accuracy	0.1%+0.1%F.S. at 0< Ouput Voltage =<75Vdc 0.05%+0.05%F.S. at 75Vdc< Ouput Voltage =<1200Vdc
Current Setting	Range	0~40A
	Resolution	0.1mA
	Accuracy	0.1%+0.10%F.S
Extra Function		
Remote Sense	Range	5V(DC), Max. Total power less than rated power
Comm. Responce.	50ms	
Graphic Display	VFD	
Operation Key Feature	Soft key, Numeric key, Rotary Knob	
Rack mount Handles	Yes	
FAN	Temperature Control	
Protection Circuits	OCP, OVP, OPP, OTP, FAN	
Interface	USB, RS485, RS232, LAN(Standard); GPIB(Optional)	
Remote Control Input/Output signal characteristics		
Remote Input signal	Not Support	
Remote output signal	Not Support	
Environmental		
Operating Temperature	0°C~40°C	
Storage Temperature	-20°C~70°C	
Altitude	2000m	
Relative Humidity	10%-90%, non-condensing	
Temperature Coefficient	100ppm/°C at Voltage, 300ppm/°C at Current	
Mechanical		
Dimensions(W*H*D)	600.0*696.0*700.0 mm	
Package Dimensions(W*H*D)	720.0*880.0*820.0 mm	
Unit Net Weight	4kg+15kg*3 (REF)	
Accessories Weight	0.4kg	
Shipping Weight	94kg+15kg*3 (REF)	
Regulatory Compliance		
CE Mark	Installation Overvltage Category II; Class II equipment; indoor use only.	

*F.S. represents the maximum value of the output range .

*N stands for the number of installed power supply units, and N is greater than 1 .

All specifications are subject to change without notice.

High Power Programmable DC Power System

SYS450VDC

MODEL		SYS450VDC12000W	SYS450VDC24000W
INPUT			
Voltage		190~265VAC	
Frequency		47~63Hz	
Phase		3 Phase,4Wire+Groud/Y Connect	
Max.Current		75A	150A
Input Power Max		15kW	28.5kW
Power Factor at 220VAC Input , Full Load		0.98 Min. Active PFC	
Efficiency		>88% Max @Full Load and Units=4kW Model	
OUTPUT			
Output Voltage		0~450V	
Output Current		0~30A	0~60A
Output Power		12kW Max	24kW Max
Load Regulation	Voltage	120mV	240mV
	Current	0.09A	0.36A
Line Regulation	Voltage	0.02%F.S.+30mV	
	Current	0.02%F.S.+15mA	
Voltage Setting	Range	0~450V	
	Resolution	10mV	
	Accuracy	0.1%+0.1%F.S. at 0< Ouput Voltage =<75Vdc 0.05%+0.05%F.S. at 75Vdc< Ouput Voltage =<1200Vdc	
Current Setting	Range	0~30A	0~60A
	Resolution	0.1mA	
	Accuracy	0.1%+0.10%F.S	
Ripple	Voltage	120mVp-p/22.5mVrms	120mVp-p/24mVrms
	Current	120mA(Full Range),20mA(TYP Value)	
MEASUREMENT			
Voltage Setting	Range	0~450V	
	Resolution	10mV	
	Accuracy	0.1%+0.1%F.S. at 0< Ouput Voltage =<75Vdc 0.05%+0.05%F.S. at 75Vdc< Ouput Voltage =<1200Vdc	
Current Setting	Range	0~30A	0~60A
	Resolution	0.1mA	
	Accuracy	0.1%+0.10%F.S	
Extra Function			
Remote Sense	Range	5V(DC), Max. Total power less than rated power	
Comm. Respondence.		50ms	
Graphic Display		VFD	
Operation Key Feature		Soft key, Numeric key, Rotary Knob	
Rack mount Handles		Yes	
FAN		Temperature Control	
Protection Circuits		OCP, OVP, OPP, OTP, FAN	
Interface		USB, RS485, RS232, LAN(Standard); GPIB(Option)	
Remote Control Input/Output signal characteristics			
Remote Input signal		Not Support	
Remote output signal		Not Support	
Environmental			
Operating Temperature		0°C~40°C	
Storage Temperature		-20°C~70°C	
Altitude		2000m	
Relative Humidity		10%-90%, non-condensing	
Temperature Coefficient		100ppm/°C at Voltage, 300ppm/°C at Current	
Mechanical			
Dimensions(W*H*D)		600.0*696.0*700.0 mm	600.0*963.0*700.0 mm
Package Dimensions(W*H*D)		720.0*880.0*820.0 mm	720.0*1160.0*820.0 mm
Unit Net Weight		54kg+15kg*3 (REF)	100.0kg+ 15kg*6 (REF)
Accessories Weight		0.4kg	
Shipping Weight		94kg+15kg*3 (REF)	160.0kg+ 15kg*6 (REF)
Regulatory Compliance			
CE Mark		Installation Overvltage Category II; Class II equipment;indoor use only.	

*F.S. represents the maximum value of the output range .

*N stands for the number of installed power supply units, and N is greater than 1 .

All specifications are subject to change without notice.

High Power Programmable DC Power System

SYS400VDC

MODEL		SYS400VDC40000W
INPUT		
Voltage	190~265VAC	
Frequency	47~63Hz	
Phase	3 Phase,4Wire+Groud/Y Connect	
Max.Current	250A	
Input Power Max	47.5kW	
Power Factor at 220VAC Input , Full Load	0.98 Min. Active PFC	
Efficiency	>88% Max @Full Load and Units=4kW Model	
OUTPUT		
Output Voltage	0~400V	
Output Current	0~120A	
Output Power	40kW Max	
Load Regulation	Voltage	400mV
	Current	1.2A
Line Regulation	Voltage	0.02%F.S.+30mV
	Current	0.02%F.S.+15mA
Voltage Setting	Range	0~400V
	Resolution	10mV
	Accuracy	0.1%+0.1%F.S. at 0< Ouput Voltage =<75Vdc 0.05%+0.05%F.S. at 75Vdc< Ouput Voltage =<1200Vdc
Current Setting	Range	0~120A
	Resolution	1mA
	Accuracy	0.1%+0.10%F.S
Ripple	Voltage	200mVp-p/30mVrms
	Current	300mA(Full Range),40mA(TYP Value)
MEASUREMENT		
Voltage Setting	Range	0~400V
	Resolution	10mV
	Accuracy	0.1%+0.1%F.S. at 0< Ouput Voltage =<75Vdc 0.05%+0.05%F.S. at 75Vdc< Ouput Voltage =<1200Vdc
Current Setting	Range	0~120A
	Resolution	1mA
	Accuracy	0.1%+0.10%F.S
Extra Function		
Remote Sense	Range	5V(DC), Max. Total power less than rated power
Comm. Respondence.	50ms	
Graphic Display	VFD	
Operation Key Feature	Soft key, Numeric key, Rotary Knob	
Rack mount Handles	Yes	
FAN	Temperature Control	
Protection Circuits	OCP, OVP, OPP, OTP, FAN	
Interface	USB, RS485, RS232, LAN(Standard); GPIB(Optional)	
Remote Control Input/Output signal characteristics		
Remote Input signal	Not Support	
Remote output signal	Not Support	
Environmental		
Operating Temperature	0°C~40°C	
Storage Temperature	-20°C~70°C	
Altitude	2000m	
Relative Humidity	10%-90%, non-condensing	
Temperature Coefficient	100ppm/°C at Voltage, 300ppm/°C at Current	
Mechanical		
Dimensions(W*H*D)	600.0*1338.0*700.0 mm	
Package Dimensions(W*H*D)	720.0*1535.0*820.0 mm	
Unit Net Weight	120.0kg+15kg*10 (REF)	
Accessories Weight	0.4kg	
Shipping Weight	200.0kg+ 15kg*10 (REF)	
Regulatory Compliance		
CE Mark	Installation Overvltage Category II ; Class II equipment; indoor use only.	

*F.S. represents the maximum value of the output range .

*N stands for the number of installed power supply units, and N is greater than 1 .

All specifications are subject to change without notice.

High Power Programmable DC Power System

SYS600VDC

MODEL	SYS600VDC12000W		SYS600VDC24000W	SYS600VDC40000W
INPUT				
Voltage	190~265VAC			
Frequency	47~63Hz			
Phase	3 Phase,4Wire+Groud/Y Connect			
Max.Current	75A	150A	250A	
Input Power Max	15kW	28.5kW	47.5kW	
Power Factor at 220VAC Input , Full Load	0.98 Min. Active PFC	0.98 Min. Active PFC	0.98 Min. Active PFC	
Efficiency	>88% Max @Full Load and Units=4kW Model			
OUTPUT				
Output Voltage	0~600V			
Output Current	0~30A	0~60A	0~100A	
Output Power	12kW Max	24kW Max	40kW Max	
Load Regulation	Voltage	240mV	480mV	800mV
	Current	30mA	60mA	100mA
Line Regulation	Voltage	0.02%F.S.+30mV		
	Current	0.02%F.S.+15mA		
Voltage Setting	Range	0~600V		
	Resolution	1mV		
	Accuracy	0.1%+0.1%F.S. at 0< Ouput Voltage =<75Vdc 0.05%+0.05%F.S. at 75Vdc< Ouput Voltage =<1200Vdc		
Current Setting	Range	0~30A	0~60A	0~100A
	Resolution	1mA		
	Accuracy	0.1%+0.10%F.S		
Ripple	Voltage	700mVp-p/80mVrms		
	Current	37.5mA(Full Range)	75mA(Full Range)	125mA(Full Range)
		15mA(TYP Value)	30mA(TYP Value)	50mA(TYP Value)
MEASUREMENT				
Voltage Setting	Range	0~600V		
	Resolution	1mV		
	Accuracy	0.1%+0.1%F.S. at 0< Ouput Voltage =<75Vdc 0.05%+0.05%F.S. at 75Vdc< Ouput Voltage =<1200Vdc		
Current Setting	Range	0~30A	0~60A	0~100A
	Resolution	1mA	1mA	10mA
	Accuracy	0.1%+0.10%F.S		
Extra Function				
Remote Sense	Range	5V(DC), Max. Total power less than rated power		
Comm. Responce.		50ms		
Graphic Display		VFD		
Operation Key Feature		Soft key, Numeric key, Rotary Knob		
Rack mount Handles		Yes		
FAN		Temperature Control		
Protection Circuits		OCP, OVP, OPP, OTP, FAN		
Interface		USB, RS485, RS232, LAN(Standard); GPIB(Option)		
Remote Control Input/Output signal characteristics				
Remote Input signal		Not Support		
Remote output signal		Not Support		
Environmental				
Operating Temperature		0°C~40°C		
Storage Temperature		-20°C~70°C		
Altitude		2000m		
Relative Humidity		10%-90%, non-condensing		
Temperature Coefficient		100ppm/°C at Voltage, 300ppm/°C at Current		
Mechanical				
Dimensions(W*H*D)		600.0*696.0*700.0 mm	600.0*963.0*700.0 mm	600.0*1338.0*700.0 mm
Package Dimensions(W*H*D)		720.0*880.0*820.0 mm	720.0*1160.0*820.0 mm	720.0*1535.0*820.0 mm
Unit Net Weight		54kg+15kg*3 (REF)	100.0kg+15kg*6 (REF)	120.0kg+15kg*10 (REF)
Accessories Weight		0.4kg		
Shipping Weight		103.5kg+15kg*3 (REF)	160.0kg+15kg*6 (REF)	200.0kg+15kg*10 (REF)
Regulatory Compliance				
CE Mark		Installation Overvltage Category II; Class II equipment; indoor use only.		

*F.S. represents the maximum value of the output range .

*N stands for the number of installed power supply units, and N is greater than 1 .

All specifications are subject to change without notice.

High Power Programmable DC Power System

SYS720VDC

MODEL		SYS720VDC24000W
INPUT		
Voltage		190~265VAC
Frequency		47~63Hz
Phase		3 Phase,4Wire+Groud/Y Connect
Max.Current		150A
Input Power Max		28.5kW
Power Factor at 220VAC Input ,Full Load		0.98 Min. Active PFC
Efficiency		>88% Max @Full Load and Units=4kW Model
OUTPUT		
Output Voltage		0~720V
Output Current		0~40A
Output Power		24kW Max
Load Regulation	Voltage	240mV
	Current	0.24A
Line Regulation	Voltage	0.02%F.S.+30mV
	Current	0.02%F.S.+15mA
Voltage Setting	Range	0~720V
	Resolution	10mV
	Accuracy	0.1%+0.1%F.S. at 0< Ouput Voltage =<75Vdc 0.05%+0.05%F.S. at 75Vdc< Ouput Voltage =<1200Vdc
Current Setting	Range	0~40A
	Resolution	0.1mA
	Accuracy	0.1%+0.10%F.S
Ripple	Voltage	240mVp-p/45mVrms
	Current	120mA(Full Range),20mA(TYP Value)
MEASUREMENT		
Voltage Setting	Range	0~720V
	Resolution	10mV
	Accuracy	0.1%+0.1%F.S. at 0< Ouput Voltage =<75Vdc 0.05%+0.05%F.S. at 75Vdc< Ouput Voltage =<1200Vdc
Current Setting	Range	0~40A
	Resolution	0.1mA
	Accuracy	0.1%+0.10%F.S
Extra Function		
Remote Sense	Range	5V(DC), Max. Total power less than rated power
Comm. Respondence.		50ms
Graphic Display		VFD
Operation Key Feature		Soft key,Numberic key,Rotary Knob
Rack mount Handles		Yes
FAN		Temperature Control
Protection Circuits		OCP, OVP, OPP, OTP, FAN
Interface		USB, RS485, RS232, LAN(Standard); GPIB(Option)
Remote Control Input/Output signal characteristics		
Remote Input signal		Not Support
Remote output signal		Not Support
Environmental		
Operating Temperature		0°C~40°C
Storage Temperature		-20°C~70°C
Altitude		2000m
Relative Humidity		10%-90%, non-condensing
Temperature Coefficient		100ppm/°C at Voltage, 300ppm/°C at Current
Mechanical		
Dimensions(W*H*D)		600.0*963.0*700.0 mm
Package Dimensions(W*H*D)		720.0*1160.0*820.0 mm
Unit Net Weight		100.0kg+15kg*6 (REF)
Accessories Weight		0.4kg
Shipping Weight		160.0kg+15kg*6 (REF)
Regulatory Compliance		
CE Mark		Installation Overvltage Category II ; Class II equipment;indoor use only.

*F.S. represents the maximum value of the output range .

*N stands for the number of installed power supply units, and N is greater than 1 .

All specifications are subject to change without notice.

High Power Programmable DC Power System

SYS750VDC

MODEL		SYS750VDC40000W
INPUT		
Voltage		190~265VAC
Frequency		47~63Hz
Phase		3 Phase,4Wire+Groud/Y Connect
Max.Current		250A
Input Power Max		47.5kW
Power Factor at 220VAC Input , Full Load		0.98 Min. Active PFC
Efficiency		>88% Max @Full Load and Units=4kW Model
OUTPUT		
Output Voltage		0~750V
Output Current		0~60A
Output Power		40kW Max
Load Regulation	Voltage	400mV
	Current	0.6A
Line Regulation	Voltage	0.02%F.S.+30mV
	Current	0.02%F.S.+15mA
Voltage Setting	Range	0~750V
	Resolution	10mV
	Accuracy	0.1%+0.1%F.S. at 0< Ouput Voltage =<75Vdc 0.05%+0.05%F.S. at 75Vdc< Ouput Voltage =<1200Vdc
Current Setting	Range	0~60A
	Resolution	0.1mA
	Accuracy	0.1%+0.10%F.S
Ripple	Voltage	200mVp-p/40mVrms
	Current	120mA(Full Range),20mA(TYP Value)
MEASUREMENT		
Voltage Setting	Range	0~750V
	Resolution	10mV
	Accuracy	0.1%+0.1%F.S. at 0< Ouput Voltage =<75Vdc 0.05%+0.05%F.S. at 75Vdc< Ouput Voltage =<1200Vdc
Current Setting	Range	0~60A
	Resolution	0.1mA
	Accuracy	0.1%+0.10%F.S
Extra Function		
Remote Sense	Range	5V(DC), Max. Total power less than rated power
Comm. Respondence.		50ms
Graphic Display		VFD
Operation Key Feature		Soft key, Numeric key, Rotary Knob
Rack mount Handles		Yes
FAN		Temperature Control
Protection Circuits		OCP, OVP, OPP, OTP, FAN
Interface		USB, RS485, RS232, LAN(Standard); GPIB(Option)
Remote Control Input/Output signal characteristics		
Remote Input signal		Not Support
Remote output signal		Not Support
Environmental		
Operating Temperature		0°C~40°C
Storage Temperature		-20°C~70°C
Altitude		2000m
Relative Humidity		10%-90%, non-condensing
Temperature Coefficient		100ppm/°C at Voltage, 300ppm/°C at Current
Mechanical		
Dimensions(W*H*D)		600.0*1338.0*700.0 mm
Package Dimensions(W*H*D)		720.0*1535.0*820.0 mm
Unit Net Weight		120.0kg+15kg*10 (REF)
Accessories Weight		0.4kg
Shipping Weight		200.0kg+15kg*10 (REF)
Regulatory Compliance		
CE Mark		Installation Overvltage Category II; Class II equipment; indoor use only.

*F.S. represents the maximum value of the output range.

*N stands for the number of installed power supply units, and N is greater than 1.

All specifications are subject to change without notice.

High Power Programmable DC Power System

SYS800VDC

MODEL	SYS800VDC12000W		SYS800VDC24000W	SYS800VDC40000W
INPUT				
Voltage	190~265VAC			
Frequency	47~63Hz			
Phase	3 Phase,4Wire+Groud/Y Connect			
Max.Current	75A	150A	250A	
Input Power Max	15kW	28.5kW	47.5kW	
Power Factor at 220VAC Input , Full Load	0.98 Min. Active PFC	0.98 Min. Active PFC	0.98 Min. Active PFC	
Efficiency	>88% Max @Full Load and Units=4kW Model			
OUTPUT				
Output Voltage	0~800V			
Output Current	0~22.5A	0~45A	0~75A	
Output Power	12kW Max	24kW Max	40kW Max	
Load Regulation	Voltage	1.5V	3V	5V
	Current	22.5mA	45mA	75mA
Line Regulation	Voltage	0.02%F.S.+30mV		
	Current	0.02%F.S.+15mA		
Voltage Setting	Range	0~800V		
	Resolution	1mV		
	Accuracy	0.1%+0.1%F.S. at 0< Ouput Voltage =<75Vdc 0.05%+0.05%F.S. at 75Vdc< Ouput Voltage =<1200Vdc		
Current Setting	Range	0~22.5A	0~45A	0~75A
	Resolution	1mA		
	Accuracy	0.1%+0.10%F.S		
Ripple	Voltage	1600mVp-p/400mVrms		
	Current	37.5mA(Full Range)	75mA(Full Range)	125mA(Full Range)
		15mA(TYP Value)	30mA(TYP Value)	50mA(TYP Value)
MEASUREMENT				
Voltage Setting	Range	0~800V		
	Resolution	1mV		
	Accuracy	0.1%+0.1%F.S. at 0< Ouput Voltage =<75Vdc 0.05%+0.05%F.S. at 75Vdc< Ouput Voltage =<1200Vdc		
Current Setting	Range	0~22.5A	0~45A	0~75A
	Resolution	1mA		
	Accuracy	0.1%+0.10%F.S		
Extra Function				
Remote Sense	Range	5V(DC), Max. Total power less than rated power		
Comm. Responce.	50ms			
Graphic Display	VFD			
Operation Key Feature	Soft key, Numeric key, Rotary Knob			
Rack mount Handles	Yes			
FAN	Temperature Control			
Protection Circuits	OCP, OVP, OPP, OTP, FAN			
Interface	USB, RS485, RS232, LAN(Standard); GPIB(Option)			
Remote Control Input/Output signal characteristics				
Remote Input signal	Not Support			
Remote output signal	Not Support			
Environmental				
Operating Temperature	0°C~40°C			
Storage Temperature	-20°C~70°C			
Altitude	2000m			
Relative Humidity	10%-90%, non-condensing			
Temperature Coefficient	100ppm/°C at Voltage, 300ppm/°C at Current			
Mechanical				
Dimensions(W*H*D)	600.0*696.0*700.0 mm	600.0*963.0*700.0 mm	600.0*1338.0*700.0 mm	
Package Dimensions(W*H*D)	720.0*880.0*820.0 mm	720.0*1160.0*820.0 mm	720.0*1535.0*820.0 mm	
Unit Net Weight	54kg+15kg*3 (REF)	100.0kg+15kg*6 (REF)	120.0kg+15kg*10 (REF)	
Accessories Weight	0.4kg			
Shipping Weight	94kg+15kg*3 (REF)	160.0kg+15kg*6 (REF)	200.0kg+15kg*10 (REF)	
Regulatory Compliance				
CE Mark	Installation Overvltage Category II; Class II equipment; indoor use only.			

*F.S. represents the maximum value of the output range .

*N stands for the number of installed power supply units, and N is greater than 1 .

All specifications are subject to change without notice.

High Power Programmable DC Power System

SYS900VDC

MODEL		SYS900VDC24000W
INPUT		
Voltage	190~265VAC	
Frequency	47~63Hz	
Phase	3 Phase,4Wire+Groud/Y Connect	
Max.Current	150A	
Input Power Max	28.5kW	
Power Factor at 220VAC Input , Full Load	0.98 Min. Active PFC	
Efficiency	> 88% Max @Full Load and Units=4kW Model	
OUTPUT		
Output Voltage	0~900V	
Output Current	0~30A	
Output Power	24kW Max	
Load Regulation	Voltage	240mV
	Current	0.18A
Line Regulation	Voltage	0.02%F.S.+30mV
	Current	0.02%F.S.+15mA
Voltage Setting	Range	0~900V
	Resolution	10mV
	Accuracy	0.1%+0.1%F.S. at 0< Ouput Voltage =<75Vdc 0.05%+0.05%F.S. at 75Vdc< Ouput Voltage =<1200Vdc
Current Setting	Range	0~30A
	Resolution	0.1mA
	Accuracy	0.1%+0.10%F.S
Ripple	Voltage	240mVp-p/45mVrms
	Current	120mA(Full Range),20mA(TYP Value)
MEASUREMENT		
Voltage Setting	Range	0~900V
	Resolution	10mV
	Accuracy	0.1%+0.1%F.S. at 0< Ouput Voltage =<75Vdc 0.05%+0.05%F.S. at 75Vdc< Ouput Voltage =<1200Vdc
Current Setting	Range	0~30A
	Resolution	0.1mA
	Accuracy	0.1%+0.10%F.S
Extra Function		
Remote Sense	Range	5V(DC), Max. Total power less than rated power
Comm. Respondence.	50ms	
Graphic Display	VFD	
Operation Key Feature	Soft key, Numeric key, Rotary Knob	
Rack mount Handles	Yes	
FAN	Temperature Control	
Protection Circuits	OCP, OVP, OPP, OTP, FAN	
Interface	USB, RS485, RS232, LAN(Standard); GPIB(Option)	
Remote Control Input/Output signal characteristics		
Remote Input signal	Not Support	
Remote output signal	Not Support	
Environmental		
Operating Temperature	0°C~40°C	
Storage Temperature	-20°C~70°C	
Altitude	2000m	
Relative Humidity	10%-90%, non-condensing	
Temperature Coefficient	100ppm/°C at Voltage, 300ppm/°C at Current	
Mechanical		
Dimensions(W*H*D)	600.0*963.0*700.0 mm	
Package Dimensions(W*H*D)	720.0*1160.0*820.0 mm	
Unit Net Weight	100.0kg+15kg*6 (REF)	
Accessories Weight	0.4kg	
Shipping Weight	160.0kg+15kg*6 (REF)	
Regulatory Compliance		
CE Mark	Installation Overvltage Category II; Class II equipment; indoor use only.	

*F.S. represents the maximum value of the output range.

*N stands for the number of installed power supply units, and N is greater than 1.

All specifications are subject to change without notice.

High Power Programmable DC Power System

SYS1200VDC

MODEL		SYS1200VDC24000W	SYS1200VDC40000W
INPUT			
Voltage		190~265VAC	
Frequency		47~63Hz	
Phase		3 Phase,4Wire+Groud/Y Connect	
Max.Current		150A	250A
Input Power Max		28.5kW	47.5kW
Power Factor at 220VAC Input , Full Load		0.98 Min. Active PFC	
Efficiency		> 88% Max @Full Load and Units=4kW Model	
OUTPUT			
Output Voltage		0~1200V	
Output Current		0~24A	0~40A
Output Power		24kW Max	40kW Max
Load Regulation	Voltage	360mV	400mV
	Current	144mA	0.4A
Line Regulation	Voltage	0.02%F.S.+30mV	
	Current	0.02%F.S.+15mA	
Voltage Setting	Range	0~1200V	
	Resolution	0.1V	
	Accuracy	0.1%+0.1%F.S. at 0< Ouput Voltage =<75Vdc 0.05%+0.05%F.S. at 75Vdc< Ouput Voltage =<1200Vdc	
Current Setting	Range	0~24A	0~40A
	Resolution	0.1mA	
	Accuracy	0.1%+0.10%F.S	
Ripple	Voltage	450mVp-p/90mVrms	400mVp-p/75mVrms
	Current	100mA(Full Range),40mA(TYP Value)	120mA(Full Range),20mA(TYP Value)
MEASUREMENT			
Voltage Setting	Range	0~1200V	
	Resolution	0.1V	
	Accuracy	0.1%+0.1%F.S. at 0< Ouput Voltage =<75Vdc 0.05%+0.05%F.S. at 75Vdc< Ouput Voltage =<1200Vdc	
Current Setting	Range	0~24A	0~40A
	Resolution	0.1mA	
	Accuracy	0.1%+0.10%F.S	
Extra Function			
Remote Sense	Range	5V(DC), Max. Total power less than rated power	
Comm. Responce.		50ms	
Graphic Display		VFD	
Operation Key Feature		Soft key, Numeric key, Rotary Knob	
Rack mount Handles		Yes	
FAN		Temperature Control	
Protection Circuits		OCP, OVP, OPP, OTP, FAN	
Interface		USB, RS485, RS232, LAN(Standard); GPIB(Optional)	
Remote Control Input/Output signal characteristics			
Remote Input signal		Not Support	
Remote output signal		Not Support	
Environmental			
Operating Temperature		0°C~40°C	
Storage Temperature		-20°C~70°C	
Altitude		2000m	
Relative Humidity		10%-90%, non-condensing	
Temperature Coefficient		100ppm/°C at Voltage, 300ppm/°C at Current	
Mechanical			
Dimensions(W*H*D)		600.0*963.0*700.0 mm	600.0*1338.0*700.0 mm
Package Dimensions(W*H*D)		720.0*1160.0*820.0 mm	720.0*1535.0*820.0 mm
Unit Net Weight		100.0kg+15kg*6 (REF)	120.0kg+15kg*10 (REF)
Accessories Weight		0.4kg	
Shipping Weight		160.0kg+15kg*6 (REF)	200.0kg+15kg*10 (REF)
Regulatory Compliance			
CE Mark		Installation Overvltage Category II; Class II equipment; indoor use only.	

*F.S. represents the maximum value of the output range.

*N stands for the number of installed power supply units, and N is greater than 1.

All specifications are subject to change without notice.